Continental Connectors Part Number Ordering Information

UMR

Model Designation
UMR, UER, URR, UWR

Connector Body (insulator) material:
Polyphenylene Sulfide, Type GST-40F, per MIL-M-24519

UER available in 90, 100 and 120 with male body only

Number of contacts:
10, 14, 20, 24, 26, 30, 36, 40, 44, 50, 56, 60, 66, 70

Note:
URR and UWR series also available in 90, 100, and 120 contacts.

Contact Termination:
0 = Standard Solder Cup
1 = Dip Solder — .110 Long
2 = Dip Solder — .140 Long
3 = Dip Solder — .172 Long
4 = Dip Solder — .234 Long
5 = Flexible Circuit — .058 Long
6 = Flexible Circuit — .100 Long

Polarizing Hardware Position:
Optional — Required Only With Y & YF "D" Shape Guides (See Chart For Polarizing Position Desired)

Deviation Code:
Consult Factory

Body & Contact Style Designation:
F = Female body & Beryllium copper female socket contact, closed entry — standard
FL = Female body & low insertion force, female socket contact closed entry, Beryllium copper
FM = Female body & half hard brass male pin contact — standard
M = Male body & phosphor bronze male pin contact — standard
MF = Male body & Beryllium copper female socket contact, closed entry — standard
MFL = Male body & low insertion force, female socket contact, closed entry, Beryllium copper — standard

Hardware Variations:
X = Round Guide — Extended Mounting Threaded
XF = Round Guide — Flush Mounting
Y = "D" Shape Guide — Extended Mounting Threaded
YF = "D" Shape Guide — Flush Mounting
KS = Turnable Screwlock — .200 Large Knob
KM = Turnable Screwlock — .500 Large Knob
KL = Turnable Screwlock — .700 Large Knob
KH = Turnable Screwlock — Hex. Socket Drive
SL = Fixed Screwlock — Extended Mounting Threaded
SF = Fixed Screwlock — Flush Mounting

Continental Connector Company, Subsidiary Of ASC Group, Inc.
53 La France Avenue ▪ Bloomfield, New Jersey ▪ 07003-5632 ▪ Phone: (973) 429-8500 ▪ FAX: (973) 743-2510