



Austin Semiconductor, Inc.  
8701 Cross Park Drive, Austin, TX 78754-4566

## Product Change Notification – PCN

PCN-0815-03

PCN ISSUE DATE	PCN #	PCN TYPE	LTB #	LTB DATE	DELIVERY FLEX (schd.)
4/9/2008	0815-03	CLASS 1	NA	NA	NA
<b>SAMPLE ORDER START DATE</b>					NA
<b>NEW MATERIAL QUALIFICATION</b>					NA
<b>NEW MATERIAL FULL PRODUCTION DATE</b>					NA

Dear Valued Customer,

Austin Semiconductor, Inc. is notifying our valued customers of a Class 1-Product Change Notification [PCN] to our 256Kb (64K x4) Fast Page Mode DRAM device group within its Hi-Reliability product family. This PCN is for a product End Of Life (EOL) announcement and effects devices within the DRAM family offered by Austin Semiconductor. Our AS4C4067 devices are listed below. This 256Kb DRAM was offered in Industrial, Automotive, Extended temp and full Military processing in 18 pin Ceramic Dual-in-line, 18 LCC and 18 LCC (low profile) package styles.

This information will be placed in the Obsolete product section of our website for those customers who may need this material for future reference.

The effected parts are identified below:

Austin PN	SMD [5962-]	Detailed Description
AS4C4067C-10/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 pin Ceramic dual-in-line, Industrial Temp
AS4C4067C-10/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 pin Ceramic dual-in-line, Automotive Temp
AS4C4067C-10/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 pin Ceramic dual-in-line, Extended Temp
AS4C4067C-10/883C	5962-9213204MVA	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 pin Ceramic dual-in-line, Full Mil Processing
AS4C4067C-12/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 pin Ceramic dual-in-line, Industrial Temp
AS4C4067C-12/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 pin Ceramic dual-in-line, Automotive Temp
AS4C4067C-12/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 pin Ceramic dual-in-line, Extended Temp
AS4C4067C-12/883C	5962-9213205MVA	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 pin Ceramic dual-in-line, Full Mil Processing
AS4C4067C-15/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 pin Ceramic dual-in-line, Industrial Temp
AS4C4067C-15/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 pin Ceramic dual-in-line, Automotive Temp
AS4C4067C-15/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 pin Ceramic dual-in-line, Extended Temp
AS4C4067C-15/883C	5962-9213206MVA	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 pin Ceramic dual-in-line, Full Mil Processing
AS4C4067EA-10/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC, Industrial Temp
AS4C4067EA-10/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC, Automotive Temp
AS4C4067EA-10/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC, Extended Temp
AS4C4067EA-10/883C	5962-9213204MYA	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC, Full Mil Processing
AS4C4067EA-12/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC, Industrial Temp
AS4C4067EA-12/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC, Automotive Temp
AS4C4067EA-12/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC, Extended Temp

<b>Austin PN</b>	<b>SMD [5962-]</b>	<b>Detailed Description</b>
AS4C4067EA-12/883C	5962-9213205MYA	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC, Full Mil Processing
AS4C4067EA-15/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC, Industrial Temp
AS4C4067EA-15/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC, Automotive Temp
AS4C4067EA-15/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC, Extended Temp
AS4C4067EA-15/883C	5962-9213206MYA	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC, Full Mil Processing
AS4C4067EC-10/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC (low profile), Industrial Temp
AS4C4067EC-10/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC (low profile), Automotive Temp
AS4C4067EC-10/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC (low profile), Extended Temp
AS4C4067EC-10/883C	5962-9213204MXA	256Kb, 64K x 4 DRAM, FPM, 100ns, 18 LCC (low profile), Full Mil Processing
AS4C4067EC-12/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC (low profile), Industrial Temp
AS4C4067EC-12/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC (low profile), Automotive Temp
AS4C4067EC-12/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC (low profile), Extended Temp
AS4C4067EC-12/883C	5962-9213205MXA	256Kb, 64K x 4 DRAM, FPM, 120ns, 18 LCC (low profile), Full Mil Processing
AS4C4067EC-15/IT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC (low profile), Industrial Temp
AS4C4067EC-15/AT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC (low profile), Automotive Temp
AS4C4067EC-15/XT	n/a	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC (low profile), Extended Temp
AS4C4067EC-15/883C	5962-9213206MXA	256Kb, 64K x 4 DRAM, FPM, 150ns, 18 LCC (low profile), Full Mil Processing

Please visit Austin Semiconductor's website at [www.austinsemiconductor.com](http://www.austinsemiconductor.com) for the latest product literature. If you have any questions regarding this Product Change Notification, please do not hesitate to contact me directly.

Regards,



Marty Steele  
Product Marketing Specialist  
Austin Semiconductor, Inc.  
8701 Cross Park Drive  
Austin, TX 78754  
Main #: 512-339-1188  
Direct #: 512-719-7259  
Email: msteele@austinsemiconductor.com